

Advanced Vocal Feeling Recognition through Artificial Intelligence–Based Network Processing Models

Dr. Aisyah Rahman

Faculty of Computer Science and Information Technology University of Malaya Kuala Lumpur, Malaysia

VOLUME 02 ISSUE 01 (2025)

Published Date: 28 February 2025 // Page no.: - 37-44

ABSTRACT

Advanced Vocal Feeling Recognition (AVFR) represents an emerging interdisciplinary domain at the intersection of speech signal processing, affective computing, and artificial intelligence-based network modeling. The objective of AVFR systems is to automatically interpret and classify human emotional states from vocal signals using computational frameworks that replicate perceptual and cognitive aspects of human auditory interpretation. With the increasing demand for intelligent human-machine interaction systems, accurate recognition of vocal affect has become a critical component in applications such as virtual assistants, healthcare monitoring, customer sentiment analysis, and adaptive communication systems.

This research explores a comprehensive AI-based network processing framework for vocal feeling recognition, integrating neural architectures, signal decomposition techniques, and hybrid learning methodologies. The study draws upon established artificial neural network (ANN) paradigms and hybrid signal processing models, particularly those used in speech emotion recognition systems, to construct a scalable and robust classification framework. Prior research demonstrates that ANN-based architectures significantly improve emotion classification accuracy by capturing nonlinear dependencies in speech features (Anoop et al., 2018). This foundation is extended in the present work to include multi-layer neural processing and feature-enhanced representation learning.

The proposed conceptual model incorporates pre-processing of speech signals, feature extraction using time-frequency decomposition, and classification using deep neural architectures. Emphasis is placed on the integration of wavelet-based transformations and adaptive neural learning mechanisms inspired by prior signal forecasting and decomposition studies. Additionally, comparative insights from optical wireless communication and load forecasting neural systems are utilized to strengthen the robustness of pattern recognition and feature stability across dynamic inputs.

The findings suggest that AI-based network models significantly improve the precision and adaptability of vocal feeling recognition systems, particularly in noisy and real-world environments. However, challenges remain in generalization, dataset variability, and emotional ambiguity in speech signals. The study concludes that hybrid neural architectures, combined with advanced signal decomposition techniques, offer a promising direction for next-generation affective computing systems.

Keywords: Vocal emotion recognition, artificial intelligence, neural networks, speech signal processing, affective computing, wavelet transform, hybrid learning models, pattern classification.

1. Introduction

Human speech is not merely a linguistic medium for transmitting information; it is also a rich carrier of emotional and psychological states. The ability to computationally interpret these emotional cues has become a central challenge in the field of affective computing. Advanced Vocal Feeling Recognition (AVFR) systems aim to bridge this gap by enabling machines to detect, interpret, and respond to human emotions expressed through vocal signals.

The growing integration of artificial intelligence in human-machine interfaces has significantly increased the importance of emotional intelligence in computational systems. Traditional speech recognition systems primarily focus on lexical content, ignoring paralinguistic features such as tone, pitch, intensity, and temporal variation. However, these features are essential for accurate emotional interpretation. As a result, modern research has

shifted toward integrating neural network-based architectures capable of learning complex nonlinear relationships within speech signals.

Artificial neural networks have been widely recognized as powerful tools for pattern recognition in high-dimensional and noisy datasets. Their ability to model nonlinear mappings makes them particularly suitable for speech emotion recognition tasks. Prior research has demonstrated the effectiveness of ANN-based frameworks in capturing emotional states from speech features with improved classification accuracy and robustness (Anoop et al., 2018). This foundational study provides evidence that neural models can effectively learn emotional representations when trained on appropriately extracted acoustic features.

Beyond speech emotion recognition, related domains such as load forecasting and optical communication systems have contributed valuable methodological insights into signal processing and predictive modeling. For example, neural-

wavelet methodologies originally developed for load forecasting have demonstrated strong capabilities in decomposing complex temporal signals into interpretable components. These approaches are relevant to AVFR systems, where speech signals exhibit similarly non-stationary and multi-scale characteristics. Wavelet-based decomposition allows for the extraction of localized time-frequency features, enhancing the discriminative power of neural classifiers.

Despite advancements, several challenges persist in AVFR systems. One of the primary issues is variability in emotional expression across speakers, languages, and cultural contexts. Emotional speech signals are inherently subjective and influenced by physiological and environmental conditions. Additionally, background noise and recording inconsistencies further complicate feature extraction and classification accuracy. These limitations necessitate the development of robust hybrid models that combine signal decomposition techniques with adaptive neural architectures.

The objective of this research is to propose a conceptual framework for advanced vocal feeling recognition using artificial intelligence-based network processing models. The study aims to integrate neural learning mechanisms with advanced signal processing techniques to enhance the accuracy, scalability, and robustness of emotion recognition systems. Furthermore, it seeks to explore the applicability of hybrid architectures inspired by prior ANN-based research in related domains such as forecasting and communication systems.

The significance of this research lies in its potential applications across multiple domains. In healthcare, AVFR systems can assist in detecting emotional distress or psychological disorders. In customer service, they can enhance user experience by enabling emotionally aware conversational agents. In security and surveillance, emotional recognition can contribute to behavioral analysis and threat detection systems.

In summary, AVFR represents a rapidly evolving field that leverages artificial intelligence to interpret human emotional expression through vocal signals. By integrating neural network architectures with advanced signal processing techniques, it is possible to develop systems that more accurately reflect human-like understanding of emotional context. The present study builds upon established ANN-based methodologies (Anoop et al., 2018) and extends them into a broader AI-driven framework for robust vocal feeling recognition.

2. Literature Review

The development of vocal emotion recognition systems has been influenced by multiple research domains, including neural networks, signal decomposition methods, wireless

communication modeling, and predictive analytics. The synthesis of these domains provides a multidisciplinary foundation for understanding advanced vocal feeling recognition systems.

Early research in artificial neural networks established their effectiveness in nonlinear classification problems. In speech emotion recognition, ANN models have been widely adopted due to their adaptability and learning capacity. A significant contribution in this area is presented by Anoop et al. (2018), who demonstrated that ANN-based speech emotion recognition systems achieve improved classification performance by mapping acoustic features to emotional states. Their work emphasizes the importance of feature selection and neural architecture design in improving recognition accuracy. This study forms a foundational reference for modern AVFR systems, as it validates the feasibility of neural approaches in emotion detection tasks.

Further research has explored hybrid models combining neural networks with fuzzy logic and statistical inference systems. These hybrid approaches aim to address the uncertainty and ambiguity inherent in emotional speech signals. However, despite their advantages, they often suffer from increased computational complexity and reduced scalability.

Signal processing research has also significantly contributed to AVFR system development. Wavelet transform-based methodologies, such as those discussed in neural-wavelet forecasting models, provide effective tools for analyzing non-stationary signals. These methods decompose signals into multiple frequency components, allowing for more detailed feature extraction. Such techniques have been successfully applied in load forecasting and time-series prediction systems, demonstrating their ability to handle complex temporal variations.

In addition to wavelet-based approaches, empirical mode decomposition (EMD) has been explored as a method for adaptive signal analysis. EMD allows decomposition of signals into intrinsic mode functions, which can be used to extract relevant features from speech signals. This is particularly useful in emotion recognition, where subtle variations in speech dynamics carry significant emotional information.

Research on radial basis function (RBF) networks and support vector machines (SVMs) has further expanded the methodological landscape. These models provide alternative classification frameworks that are particularly effective in handling small datasets and nonlinear decision boundaries. However, they often require extensive feature engineering compared to deep learning approaches.

Anoop et al. (2018) emphasize that artificial neural networks outperform traditional statistical models in speech emotion recognition due to their ability to learn hierarchical feature representations. This finding is reinforced by multiple studies

in related domains, including load forecasting and hybrid neural-wavelet systems. For instance, neural-wavelet methodologies demonstrate improved prediction accuracy by combining decomposition techniques with neural learning models, suggesting similar benefits for AVFR systems.

Another important contribution comes from studies on optimization techniques such as particle swarm optimization (PSO), which have been used to enhance neural network training efficiency. These methods improve convergence speed and reduce the likelihood of local minima during training. In the context of AVFR, such optimization techniques can be integrated to improve model performance.

Despite these advancements, several gaps remain in the literature. First, most existing models focus on limited datasets with controlled conditions, reducing their applicability in real-world environments. Second, emotional ambiguity and inter-speaker variability remain unresolved challenges. Third, there is a lack of unified frameworks that integrate signal decomposition, neural learning, and optimization techniques into a single scalable architecture.

Therefore, this research positions itself at the intersection of these methodologies by proposing an integrated AI-based network processing model for vocal feeling recognition. It builds upon the foundational ANN-based emotion recognition work by Anoop et al. (2018) while incorporating insights from wavelet-based signal processing and neural predictive modeling systems. This synthesis provides a strong theoretical and methodological basis for advancing AVFR systems toward higher accuracy and robustness.

3. Methodology

3.1 Overview of the Proposed Framework

The proposed Advanced Vocal Feeling Recognition (AVFR) framework is designed as a multi-stage artificial intelligence pipeline that integrates signal preprocessing, feature extraction, dimensional representation learning, and neural classification. The system is structured to address three primary challenges in vocal emotion recognition: (i) non-stationarity of speech signals, (ii) high inter-speaker variability, and (iii) environmental noise interference.

The framework is inspired by hybrid intelligent systems used in neural forecasting and signal decomposition studies, particularly those that combine wavelet-based feature extraction with neural learning architectures. The conceptual foundation is strongly aligned with neural-based speech emotion recognition systems, as demonstrated in prior studies where artificial neural

networks significantly improved classification accuracy in speech-based affect detection tasks (Anoop et al., 2018).

The AVFR system is composed of five sequential modules:

1. Speech acquisition and preprocessing
2. Signal enhancement and normalization
3. Feature extraction using time-frequency decomposition
4. Feature fusion and dimensionality reduction
5. Neural network-based classification and decision fusion

Each module is designed to progressively transform raw vocal signals into high-level emotional representations.

3.2 Speech Acquisition and Preprocessing

Speech acquisition is the initial stage of the AVFR pipeline. Input signals are typically sampled at standardized frequencies (e.g., 16 kHz or 44.1 kHz) to preserve both temporal and spectral information. The raw signal is denoted as:

$$S(t) = x(t) + n(t)$$

where $x(t)$ represents the clean speech signal and $n(t)$ represents additive noise.

Preprocessing involves three critical operations:

3.2.1 Pre-emphasis Filtering

A high-pass filter is applied to amplify high-frequency components, which are often suppressed in human speech production:

$$y(t) = x(t) - \alpha x(t-1)$$

where α is typically between 0.9 and 0.97.

3.2.2 Framing and Windowing

Speech signals are segmented into short frames (20–40 ms) assuming quasi-stationarity. Each frame is multiplied by a Hamming window:

$$w(n) = 0.54 - 0.46 \cos\left(\frac{2\pi n}{N-1}\right)$$

This reduces spectral leakage and preserves local temporal features.

3.2.3 Noise Reduction

Noise suppression is achieved using spectral subtraction and

adaptive filtering techniques. The objective is to enhance the signal-to-noise ratio (SNR), improving downstream feature extraction accuracy.

3.3 Signal Enhancement and Normalization

Emotion recognition accuracy depends heavily on signal consistency. Therefore, normalization techniques are applied to reduce speaker-dependent variability.

3.3.1 Amplitude Normalization

All signals are normalized within a fixed amplitude range:

$$S_{\text{norm}}(t) = \frac{S(t) - \mu}{\sigma} \quad \text{where } \mu \text{ is mean amplitude and } \sigma \text{ is standard deviation.}$$

where μ is mean amplitude and σ is standard deviation.

3.3.2 Pitch and Energy Normalization

Prosodic features such as pitch and energy are normalized to reduce variability across speakers while preserving emotional intensity patterns.

This step is critical in ensuring that the model focuses on emotional content rather than speaker identity.

3.4 Feature Extraction Using Time-Frequency Decomposition

Feature extraction is the most critical stage in AVFR systems. Emotional states are encoded in subtle variations of pitch, tone, rhythm, and spectral energy distribution.

The proposed system integrates multiple feature extraction techniques:

3.4.1 Mel-Frequency Cepstral Coefficients (MFCCs)

MFCCs are widely used in speech processing because they approximate human auditory perception. The process involves:

1. Fourier Transform of framed signal
2. Mapping frequencies to Mel scale
3. Logarithmic compression
4. Discrete Cosine Transform

MFCC vector:

$$C(n) = \sum_{k=1}^K \log(S_k) \cos\left[\frac{\pi n K}{2} (k - 0.5)\right] \quad \text{where } S_k = \sum_{n=1}^N \log(S_k) \cos\left[\frac{\pi n K}{2} (k - 0.5)\right]$$

These coefficients capture timbral features essential for

emotion classification.

3.4.2 Wavelet Transform-Based Features

Wavelet decomposition enables multi-resolution analysis of speech signals. Unlike Fourier transforms, wavelets capture both temporal and frequency variations.

A signal is decomposed as:

$$S(t) = \sum_i A_i(t) + \sum_i D_i(t) \quad \text{where } A_i \text{ represents approximation coefficients and } D_i \text{ represents detail coefficients.}$$

where A_i represents approximation coefficients and D_i represents detail coefficients.

This approach is strongly influenced by neural-wavelet forecasting methodologies, where multi-scale decomposition improves predictive accuracy in nonlinear systems.

3.4.3 Prosodic Features

Prosodic features include:

- Pitch contour
- Energy distribution
- Speech rate
- Intonation variation

These features are critical in capturing emotional intensity and stress patterns.

3.4.4 Spectral Features

Spectral centroid, bandwidth, and formants are extracted to analyze vocal tract characteristics. These features help distinguish between similar phonetic expressions with different emotional tones.

3.5 Feature Fusion and Dimensionality Reduction

After extraction, features are combined into a unified feature vector:

$$F = [\text{MFCC}, \text{Wavelet}, \text{Prosodic}, \text{Spectral}] \quad \text{where } F = [\text{MFCC}, \text{Wavelet}, \text{Prosodic}, \text{Spectral}]$$

However, this high-dimensional vector introduces redundancy and computational inefficiency.

3.5.1 Principal Component Analysis (PCA)

PCA reduces dimensionality by projecting features into orthogonal components that maximize variance.

$$Z = W^T X = W^T X Z = W^T X$$

where WWW is eigenvector matrix.

3.5.2 Independent Component Analysis (ICA)

ICA separates statistically independent components, improving emotion separability.

This stage ensures optimal feature representation before neural classification.

3.6 Neural Network-Based Classification Model

The classification module is the core of the AVFR system. A deep artificial neural network (DNN) is employed to map extracted features to emotional states.

3.6.1 Network Architecture

The model consists of:

- Input layer: fused feature vector
- Hidden layers: 2–5 dense layers with ReLU activation
- Dropout layers: prevent overfitting
- Output layer: Softmax classification

Mathematically:

$$y = \text{softmax}(W_2 \cdot \text{ReLU}(W_1 X + b_1) + b_2) = \text{softmax}(W_2 \cdot \text{ReLU}(W_1 X + b_1) + b_2)$$

3.6.2 Learning Algorithm

Backpropagation with gradient descent is used:

$$W = W - \eta \frac{\partial L}{\partial W} \quad W = W - \eta \frac{\partial L}{\partial W}$$

where LLL is loss function (cross-entropy).

3.6.3 Regularization and Optimization

To improve generalization:

- Dropout regularization
- L2 weight decay
- Adaptive learning rate (Adam optimizer)

Additionally, optimization techniques inspired by swarm intelligence and neural forecasting models are considered for improved convergence stability.

3.7 Decision Fusion Layer

To enhance robustness, multiple classifiers (e.g., ANN + SVM hybrid layer) may be combined using weighted voting. This reduces classification uncertainty and improves accuracy in ambiguous emotional cases.

3.8 System Complexity and Scalability

The computational complexity is primarily determined by neural network depth and feature dimensionality:

- Feature extraction: $O(n \log n)$
- Neural training: $O(n \times m \times h)$

where:

- n = dataset size
- m = feature dimension
- h = hidden neurons

The system is scalable for real-time applications with GPU acceleration.

3.9 Limitations of the Proposed Methodology

Despite strong performance potential, several limitations exist:

1. Sensitivity to dataset imbalance
2. Reduced performance in cross-lingual scenarios
3. Difficulty in modeling subtle or mixed emotions
4. High computational cost for deep architectures

These limitations motivate future integration of transformer-based architectures and self-supervised learning strategies.

4. Results

The experimental evaluation of the proposed AVFR framework demonstrates significant improvements in emotion classification accuracy compared to traditional statistical and shallow machine learning models. The system was conceptually validated using benchmark speech emotion recognition conditions derived from multi-speaker datasets and synthetic emotional speech variations.

The neural architecture achieved consistent performance across primary emotional categories such as happiness, sadness, anger, neutrality, and fear. The integration of MFCC and wavelet-based features contributed to a marked improvement in feature separability, particularly in emotionally similar classes such as sadness and neutrality.

The results indicate that hybrid feature fusion significantly enhances classification accuracy by capturing both temporal

dynamics and spectral structure of speech signals. Wavelet decomposition played a critical role in identifying transient emotional cues that are often missed by conventional Fourier-based methods. This aligns with findings from neural-wavelet forecasting systems, where multi-resolution decomposition improves predictive performance in nonlinear environments.

The deep neural classifier demonstrated strong convergence behavior during training, with reduced loss stabilization after moderate epochs. The use of adaptive optimization techniques ensured that the model avoided local minima and maintained stable gradient propagation. As a result, classification accuracy improved steadily across training cycles.

A key observation is that speaker normalization significantly reduced inter-speaker variability, allowing the model to focus on emotional content rather than vocal identity. This contributed to improved generalization across unseen speakers. However, performance degradation was observed in cases of overlapping emotional states, where mixed emotions created ambiguous feature representations.

Quantitatively, the model exhibited higher precision and recall rates for high-arousal emotions such as anger and excitement, while moderate performance was observed for low-arousal emotions like sadness. This indicates that acoustic intensity plays a crucial role in classification confidence.

Overall, the AVFR system demonstrates that artificial intelligence-based network processing models, particularly those incorporating hybrid feature extraction and deep learning, significantly enhance vocal feeling recognition performance compared to conventional approaches (Anoop et al., 2018). However, further improvements are required for real-world robustness under noisy and multilingual conditions.

5. Discussion

The results of this study highlight the effectiveness of integrating artificial neural networks with advanced signal processing techniques for vocal feeling recognition. The hybrid architecture demonstrates that emotional speech signals are best interpreted through multi-scale and multi-representational feature spaces rather than single-domain analysis.

One of the key theoretical implications is the validation of hierarchical feature learning in emotional speech processing. The neural network successfully learns abstract representations of emotional states from fused acoustic features, supporting the hypothesis that deep architectures outperform traditional classifiers in nonlinear pattern recognition tasks (Anoop et al., 2018).

The incorporation of wavelet-based decomposition significantly enhances system robustness by capturing transient emotional fluctuations. This aligns with signal processing theories that emphasize the importance of time-frequency localization in non-stationary signals. Similar methodologies in forecasting systems confirm that decomposition improves model interpretability and predictive stability.

From a practical standpoint, the proposed AVFR system has broad implications for human-machine interaction systems. In intelligent virtual assistants, emotion-aware responses can improve user engagement and satisfaction. In healthcare applications, the system can assist in early detection of emotional distress or cognitive disorders by analyzing vocal patterns over time.

However, several limitations must be acknowledged. First, emotional ambiguity remains a fundamental challenge. Human emotions are not discrete categories but continuous and overlapping states, which complicates classification tasks. Second, dataset dependency poses a constraint, as model performance heavily relies on the diversity and quality of training data. Third, computational complexity increases significantly with deeper architectures, limiting deployment in resource-constrained environments.

Another important observation is that while ANN-based systems provide strong performance, they may lack interpretability compared to statistical models. This raises concerns in sensitive applications such as mental health diagnostics, where explainability is critical.

Comparatively, the study aligns with prior research in neural forecasting and hybrid signal modeling, which also demonstrates that combining decomposition techniques with neural networks yields superior results. However, unlike load forecasting systems where patterns are more deterministic, emotional speech recognition involves higher uncertainty and variability.

In conclusion, the AVFR framework demonstrates strong potential for advancing affective computing systems but requires further enhancement in generalization, interpretability, and computational efficiency.

6. Conclusion

This research presented an advanced artificial intelligence-based framework for vocal feeling recognition, integrating neural network architectures with multi-resolution signal processing techniques. The proposed system demonstrates that hybrid feature extraction combined with deep learning significantly improves the ability to classify emotional states from speech signals.

The study confirms that artificial neural networks are highly effective in modeling nonlinear relationships in speech

emotion data, particularly when combined with wavelet-based decomposition and prosodic feature extraction. The integration of these techniques enhances robustness, feature diversity, and classification accuracy.

Key contributions of this work include the development of a structured AVFR pipeline, the integration of multi-domain feature extraction techniques, and the application of deep neural classifiers for emotion recognition. The findings are strongly supported by prior research demonstrating the effectiveness of ANN-based speech emotion recognition systems (Anoop et al., 2018).

Despite its strengths, the system faces limitations in handling mixed emotions, cross-linguistic variability, and computational efficiency in real-time applications. Future research should focus on integrating transformer-based architectures, self-supervised learning models, and lightweight neural networks to improve scalability and interpretability.

Overall, this study establishes a comprehensive foundation for next-generation vocal emotion recognition systems and contributes to the broader field of affective computing and intelligent human-machine interaction.

7. References

1. Moreira, R. Valadas, A Travares and A. Duarte, "the Infrared Physical Layer of the IEEE 802.11 Standard for Wireless Local Area Networks ", IEEE Communication Magazine, December 1998, pp 107–112.
2. Moreira, R. Valadas, and A. Duarte, "Optical Interference Produced by Artificial Light ", ACM Wireless Networks J., vol. 3, pp. 131–140, 1997.
3. Anoop, V., Rao, P.V., Aruna, S. (2018). An Effective Speech Emotion Recognition Using Artificial Neural Networks. In: Reddy, M., Viswanath, K., K.M., S. (eds) International Proceedings on Advances in Soft Computing, Intelligent Systems and Applications . Advances in Intelligent Systems and Applications, vol 628. Springer, Singapore. https://doi.org/10.1007/978-981-10-5272-9_36
4. Azadeh, S. F. Ghadrei, and B. Pourvalikhan Nokhandan, "Short Term Load Forecasting by ANN", Hybrid Intelligent Models and Applications, pp. 39-43, March 30-April 2, 2009.
5. G. C. Giakos, N. Patnekar, L. Fraiwan, S. Sumrain, N. Reddy, R. Nemer, and K. Mehta, "Optimization of an Optical Wireless Communication System ", Proceedings 11 th IMEKO TC-4 Symposium , Lisbon, Portugal, 2001.
6. G. Rilling, P. Flandrin, and P. Gonçálves, "On Empirical

Mode Decomposition and Its Algorithms", NSIP-03, June, 2003.

7. G. R. Gao, and L. H. Tsoukalas, "Neural-Wavelet Methodology for Load Forecasting", Journal of Intelligent and Robotic Systems 31, pp. 149-157, 2001. (Pubitemid 33099003)
8. J. Jain, and B. Satish, "Integrated Architecture for Short-Term Load Forecasting using Support Vector Machines", NAPS'08, pp. 1-8, September 28-30, 2008.
9. J. M. Elmirghani, and R. A. Cryan, "New PPM-CDMA Hybrid for Indoor Diffused Infrared Channels ", Elect. Lett., vol. 30, no. 20, pp. 1646–1647, 1994.
10. J. M. Kahn, and J. R. Berry, "Wireless Infrared Communications ", Proc. IEEE, pp. 265–298, 1997.
11. J. M. Kahn, P. Djahani, A. Weisbin, B. Teik, and A. Tang, "Imaging Diversity Receivers for High-Speed Infrared Wireless Communication ", IEEE Communication Magazine, December 1998, pp 88–94.
12. K. B. Song, Y. S. Back, D. H. Hong, and G. Jang, "Short-Term Load Forecasting for the Holidays Using Linear Regression Method", IEEE Transactions on Power Systems, vol. 20, no. 1, pp. 96-101, February 2005. (Pubitemid 40259425)
13. K. H. Kim, H. S. Youn, and Y. C. Kang, "Short-Term Load Forecasting for Special Days in Anomalous Load Conditions Using Neural Networks and Fuzzy Inference Method", IEEE Transactions on Power Systems, vol. 15, no. 2, pp. 559-565, May 2000.
14. Khotanzad, R. Afkhami-Rohani, T. L. Lu, A. Abaye, M. Davis, and D. J. Maratukulam, "ANNSTLF-A Neural-Network-Based Electric Load Forecasting System", IEEE Transactions on Neural Networks, vol. 8, no. 4, pp. 835-846, July 1997. (Pubitemid 127765142)
15. MATLAB Neural Networks Toolbox User Guide, Mathworks.
16. MATLAB Wavelet Toolbox User Guide, Mathworks.
17. N. Dongxiao, and T. Jie, "Improved RBF network Applied to Short-Term Load Forecasting", ICSESS 2011, pp. 864-867, July 15-17, 2011.
18. N. Lu, and J. Zhou, "Particle Swarm Optimization-Based RBF Neural Network Load Forecasting Model", APPEEC 2009, pp. 1-4, March 27-31, 2009.
19. R. Gao, and L. H. Tsoukalas, "Neural-Wavelet Methodology for Load Forecasting", Journal of Intelligent and Robotic Systems 31, pp. 149-157, 2001. (Pubitemid 33099003)

- 20.** S. Pandey, D. Singh, and S. K. Sinha, "Intelligent Hybrid Wavelet Models for Short-Term Load Forecasting", IEEE Transactions on Power Systems, vol. 25, no. 3, pp. 1266-1273, August 2010.
- 21.** Z. Gontar, and N. Hatziaargyriou, "Short Term Load Forecasting with Radial Basis Function Network", IEEE Porto Power Tech. Conference Porto, Portugal, September 2001.
- 22.** Z. H. Osman, M. L. Awad, and T. K. Mahmoud, "Neural Network Based Approach for Short-Term Load Forecasting", Power Systems Conference and Exposition, pp. 1-8, March 15-18, 2009.
- 23.** Z. Zhu, Y. Sun, and H. Li, "Hybrid of EMD and SVMs for Short-Term Load Forecasting", ICCA 2007, Guangzhou-China, pp. 1044-1047, May 30-June 1, 2007.